



Product Highlights

P-Iris & Motorized Lens

Motorized control of the P-Iris lens gives finer contrast and clearer image quality lighting and allows remote zoom and focus

Full HD Resolutions at 30 fps

The 2 megapixel progressive CMOS sensor captures all the details with smooth, high definition video and still images

Wide Dynamic Range

Wide Dynamic Range technology neutralizes imperfect lighting, providing clear images with the right amount of contrast even for backlit subjects



DCS-7513 Full HD WDR Outdoor Bullet IP Camera

Features

Exceptional Video Quality

- 1/2.8" 2 megapixel progressive CMOS sensor
- 2.8 - 12 mm motorized varifocal lens
- Up to Full HD resolution of 1920 x 1080 at 60 fps (WDR off) or 30 fps (WDR on)
- Remote Zoom and Focus
- Support for face detection
- P-Iris technology
- Wide Dynamic Range
- H.264, MPEG-4, MJPEG codec support for streaming and recording

Outdoor Placement

- Built-in IR LED illuminator with a 90 foot range, smart detection, and auto adjustment for use in dark areas
- Built-in heating and cooling ensure the camera can work in a range of climates from -40° to 122 °F
- Cable management bracket
- IP68 certified housing
- Glare reducing sun shield

Flexibility and Connectivity

- microSD Card slot for onboard storage
- 10/100 Fast Ethernet port with PoE
- Digital Input and Output connector for connections to external devices such as alarm relays
- Audio in and out jacks can be connected to a microphone and speaker for 2-way communication

Overview

The D-Link DCS-7513 Full HD WDR Day & Night Outdoor Network Camera is a high-definition professional surveillance and security solution suitable for small, medium, and large enterprises. The camera uses a high sensitivity 2 megapixel progressive scan CMOS sensor with a motorized P-Iris lens and onboard WDR image enhancement to deliver truly superior quality video in all conditions. The all-in-one rugged design makes this camera ideal for reliable deployment in surveillance applications without the need for accessories

High-Quality Video

The DCS-7513 is equipped with a P-Iris lens that controls the iris with extreme precision. Its built-in stepping motor maintains the iris opening at an optimal level at all times, resulting in superior image quality, clarity, and depth of field. The remote focus function eliminates the need for manual focusing at the camera's position and allows you to make adjustments from any computer. The camera also supports face detection for more accurate monitoring. To maximize bandwidth efficiency and improve image quality, the DCS-7513 provides real-time video compression using the H.264, MPEG-4 and MJPEG codecs and supports three separate profiles for simultaneous video streaming and recording. This versatility enables a wide variety of security applications, such as monitoring public areas to detect incidents and to coordinate responses, enforcing access control to restricted areas, deterring criminal activity, or monitoring inventory. Furthermore, bandwidth requirements can be adjusted in real-time over the network, and recorded video files can be saved to a network attached storage (NAS) device or microSD card.

Continuous Monitoring

The DCS-7513 WDR image enhancement gives you improved image quality in environments with uneven or difficult lighting, so you can identify subjects that are backlit or in brightly lit areas. In low-light situations, the IR cut filter automatically slides out of the way to use all available light. The DCS-7513 is also built with IR LED illuminators with a 90 foot range along with smart detection and auto adjustment allowing the camera to keep watch even in complete darkness. These elements combine to make the DCS-7513 an ideal solution for 24-hour surveillance.

Robust Management Software

The DCS-7513 includes D-ViewCam, a complete surveillance software package that enables you to view, manage, and record up to 32 cameras on a single computer from a central location. Recordings and e-mail alerts can be triggered through motion detection or events triggered by digital input devices, keeping administrators informed of any unusual activity.

Connectivity

The DCS-7513 has a built-in 802.3af compliant PoE module that eases installation by providing power and networking connectivity with a single cable reducing the need to drill holes or lay additional cabling. In addition, the included digital input and output connector enables connections to external devices such as IR sensors, switches and alarm relays.

Technical Specifications		
Camera		
Camera Hardware Profile	<ul style="list-style-type: none"> • 1/2.8" 2 Megapixel progressive CMOS sensor • 90 feet IR illumination distance • IR smart detection and auto adjustment • Minimum illumination: 0 lux with IR LEDs on • Built-in Infrared-Cut Removable (ICR) Filter module • 10x digital zoom • Support for face detection 	<ul style="list-style-type: none"> • 2.8 to 12 mm motorized varifocal lens • Aperture: F1.4 • Angle of view (16:9) <ul style="list-style-type: none"> • (H) 33° to 108° • (V) 19° to 57° • (D) 39° to 134°
Camera Housing	<ul style="list-style-type: none"> • IP68 compliant weatherproof housing 	<ul style="list-style-type: none"> • Cable management bracket
Image Features	<ul style="list-style-type: none"> • Configurable image size, quality, frame rate, and bit rate • Time stamp and text overlays • Configurable motion detection windows 	<ul style="list-style-type: none"> • Configurable privacy mask zones • Configurable shutter speed, brightness, saturation, contrast, and sharpness
Video Compression	<ul style="list-style-type: none"> • Simultaneous H.264/MPEG-4/MJPEG format compression 	<ul style="list-style-type: none"> • JPEG for still images
Video Resolution	<ul style="list-style-type: none"> • 16:9 at 1920 x 1080, 1280 x 720, 960 x 560, 640 x 360, 320 x 176 up to 60 fps (WDR off) or 30 fps (WDR on) • 4:3 at 1280 x 960, 1024 x 768, 800 x 600, 640 x 480, 320 x 240 up to 60 fps (WDR on) or 30 fps (WDR off) 	
Audio Support	<ul style="list-style-type: none"> • G.711 	<ul style="list-style-type: none"> • AAC
External Device Interface	<ul style="list-style-type: none"> • 10/100 BASE-TX Ethernet port with PoE (Class 3) • 1 DI / 1 DO 	<ul style="list-style-type: none"> • microSD card slot • Audio input/output
Network		
Network Protocols	<ul style="list-style-type: none"> • IPv6 • IPv4 • TCP/IP • UDP • ICMP • DHCP client • NTP client (D-Link) • DNS client • DDNS client (D-Link) • SMTP client • FTP client 	<ul style="list-style-type: none"> • HTTP / HTTPS • Samba client • PPPoE • UPnP port forwarding • RTP / RTSP / RTCP • IP filtering • QoS • CoS • IGMP • ONVIF compliant
Security	<ul style="list-style-type: none"> • Administrator and user group protection • Password authentication 	<ul style="list-style-type: none"> • HTTP and RTSP digest encryption

System Management	
System Requirements for Web Interface	<ul style="list-style-type: none"> • Browser: <ul style="list-style-type: none"> - Internet Explorer - Chrome - Firefox - Safari
Event Management	<ul style="list-style-type: none"> • Motion detection • Event notification and uploading of snapshots/video clips via e-mail or FTP • Supports multiple SMTP and FTP servers • Multiple event notifications • Multiple recording methods for easy backup
Remote Management	<ul style="list-style-type: none"> • Take snapshots/video clips and save to local hard drive or NAS via web browser • Configuration interface accessible via web browser
Operating System	<ul style="list-style-type: none"> • Windows 10/8/7/Vista/XP/2000
D-ViewCam™ System Requirements	<ul style="list-style-type: none"> • Operating System: Microsoft Windows 8/7/Vista/XP • Web Browser: Internet Explorer 7 or higher • Protocol: Standard TCP/IP
D-ViewCam™ Software Functions	<ul style="list-style-type: none"> • Remote management • Control and manage up to 32 cameras • View up to 32 cameras on one screen • Management functions provided in web interface • Scheduled motion triggered and manual recording triggers
General	
Weight	<ul style="list-style-type: none"> • 3.4 lbs with bracket and sun shield (1.54 kg)
External Power Adapter	<ul style="list-style-type: none"> • Input: 100 to 240 V AC, 50/60 Hz • Output: 12 V 1.25 A
Power Consumption	<ul style="list-style-type: none"> • 11 watts ± 5 %
Temperature	<ul style="list-style-type: none"> • Operating: -40 to 122 °F (-40 to 50 °C) • Storage: -4° to 158° F (-20 to 70° C)
Humidity	<ul style="list-style-type: none"> • Operating: 20% to 80% non-condensing • Storage: 5% to 95% non-condensing
Certifications	<ul style="list-style-type: none"> • CE • CE LVD • FCC • C-Tick
Dimension	<p>The technical drawings show the following dimensions:</p> <ul style="list-style-type: none"> Front View: Width 3.8" (97.5 mm), Height 9.8" (249.1 mm), Bottom Width 3.9" (100 mm). Side View: Lens Tube Length 12.5" (316.5 mm), Lens Tube Diameter 8.8" (223.5 mm), Lens Tube Height 3.6" (90.7 mm), Mounting Arm Length 8.5" (216.7 mm), Mounting Arm Height 4.7" (120 mm).

DCS-7513 Full HD WDR Day & Night Outdoor Network Camera

Warranty	
Warranty	5-Year Warranty ¹
Order Information	
Part Number	Description
DCS-7513	Full HD WDR Day & Night Outdoor Network Camera

¹5-Year Warranty available only in the USA.

U.S.A. | 17595 Mt. Herrmann Street | Fountain Valley, CA 92708 | 800.326.1688 | dlink.com **Canada** | 2525 Meadowvale Blvd | Mississauga, ON L5N 5S2 | 800.361.5265 | dlink.ca

©2017 D-Link Corporation/D-Link Systems, Inc. All rights reserved. D-Link, the D-Link logo, mydlink, ShareCenter, the D-Link RoHS logo and trademarks or registered trademarks of D-Link Corporation or its subsidiaries in the United States and/or other countries. Other trademarks or registered trademarks are the property of their respective owners. Visit www.dlink.com for more details.

Updated 04/2017
DCS-7513_REVB_DATASHEET_04252017_2.00_US

