

S&G® 2890B Lock

UL APPROVED

The S&G 2890B—with UL approved components—provides both secure entry and life safety in one integrated solution. It works in conjunction with both GSA approved combination locks to provide the highest level of safety and security of SCIFs. With an innovative life safety component, the S&G 2890B also provides single motion egress at all times via a panic bar or lever.












FEATURES

- **FLEXIBLE DESIGN:** Interfaces with one of the electromechanical combination locks: S&G 2740B or X-10. (*Combination lock sold separately.*)
- **STURDY INSTALLATION:** Heavy-duty, adjustable mounting system provides a strong, solid install to prevent door collapse.
- **NON-HANDED:** Designed to meet every need: right-hand, left-hand, in-swing and out-swing doors made of metal or wood.
- **SMOOTH OPERATION:** Heavy-duty, surface mounted strike with integral roller for secure, smooth operation.
- **PINCH-PROOF STRIKES:** Multiple strike options available for in-swing, out-swing and double door applications.
- **LASTING DURABILITY:** Levers tested to 1M cycles and panic bar to 500K cycles for reliability and longevity.
- **MODULAR DESIGN:** All six configurations are based on the same modular platform, providing a faster, standardized installation in facilities with multiple openings.
- **HIGHEST FIRE RATING:** 3-hour UL fire rating that is highest on the market in this segment.
- **CERTIFICATIONS:** NFPA 101 Life Safety, UL 305, BHMA, UL Fire 10B and 10C.
- **WARRANTY:** The S&G 2890B is backed by a 5-year product warranty*

*When used with the S&G 2740B lock.

S&G 2890B Lock


400 Series with UL Approved Components

2890B (interior)	Type (Definition)/ Part Number	Application	Life Safety Exit	Access Control (AC) Integration Options	Interior Bolt Blocking on Retracted 2740B
Center Locking Module with Lever  <ul style="list-style-type: none"> FF-L-2740B dial lock combined with a sturdy ADA-compliant release handle on interior Secondary locking option: Mechanical keys 	Type I (PDPL) 2890-410	Office	Lever	Rim Cylinder	 Keyed Cam Lock
	Type II (PDPL) 2890-420	Office	Lever	Electronic with Key Bypass	 Keyed Cam Lock
Center Locking Module with Panic Bar  <ul style="list-style-type: none"> Single-push panic bar Secondary locking option: access control system or mechanical keys 	Type III (PDLAP) 2890-430	Conference Room	Panic Bar	Rim Cylinder	 Keyed Cam Lock
	Type IV (PDLAP) 2890-440	Conference Room	Panic Bar	Electronic with Key Bypass	 Keyed Cam Lock
Center Locking Module with Lever  <ul style="list-style-type: none"> Deadbolt 	Type V (ADB) 2890-450	Storage Closet	Lever	NA	 Keyed Cam Lock
	Type VI (ADB) 2890-460	Storage Closet	Lever	NA	 Keyless Thumbturn


PDPL: Pedestrian Door Preassembled Lock **PDLAP:** Pedestrian Door Lock Assembly Panic **ADB:** Auxiliary Deadbolt

THE S&G 2890B OFFERS A VARIETY OF STRIKE OPTIONS


All units ship with a #2 strike.




#1 STRIKE for single or double door in-swing mortise
PRODUCT NO. 2890-601



#2 STRIKE for single door out-swing
PRODUCT NO. 2890-602



#3 STRIKE for single or double door in-swing surface
PRODUCT NO. 2890-603



#9 STRIKE for double door out-swing surface
PRODUCT NO. 2890-609

For a 5-year warranty, all six types can be installed with an S&G 2740B high-security lock (sold separately). Installing 2890B with X-10 provides 2-year warranty. 3-Hour UL Fire Rated with either combination lock.

www.sargentandgreenleaf.com/2890B

Corporate Headquarters: One Security Drive • Nicholasville, Kentucky 40356 • USA • Tel. 859-885-9411, Fax 859-887-2057
Except as otherwise noted, all trademarks in this data sheet are trademarks of Stanley Black and Decker or its affiliates in the U.S. and elsewhere.
© denotes a trademark registered in the U.S. Patent and Trademark Office. Patents Pending.



SG2890.S2.Rv.04.11.16
© 2016 Sargent & Greenleaf, Inc.