Compt. RegulatoR.

The RegulatoR is available in two versions: self-locking and manual locking.

Self-locking features **SlamCam**, a spring loaded latch, which allows the user simply to close the cabinet door or drawer — no need to return the knob to the locked position.

Manual locking version, which uses existing CompX National cams, requires users to rotate the knob into the unlocked and locked positions.







How to build a RegulatoR part number

For example, REG-S-L-5:

Standard length knob, Self-locking, Left hand mount, 1-3/4" cylinder, standard silver finish **REG** = RegulatoR standard length knob

REGS = RegulatoR short length knob

S = Self-locking - featuring SlamCAM

M = Manual locking - use with standard CompX National cams

L = Left hand mount, door application – hinge on left side when facing cabinet

R = Right hand mount, door application - hinge on right side when facing cabinet

V = Vertical mount, door application (keypad located above locking point)

T = Top vertical mount, door application (keypad located below locking point)

1 = 7/16" cylinder length (up to 1/8" material thickness)

3 = 1-3/16" cylinder length (up to 7/8" material thickness)

5 = 1-3/4" cylinder length (up to 1-7/16" material thickness)

BK = Matte black housing & knob (optional; only use if black finish is desired)

Misc. RegulatoR part numbers:

REG-KIT-KNOB - replacement knob kit

REG-KIT-KNOBS - replacement short knob kit

213005000000J - replacement battery door

Location of door hinges determines hand of door when facing door; i.e. if hinges are on the right, order right hand mount.

