

► **PACKAGING INCLUDES**

- UL Listed 2 3/4" Backset, 2 1/4" x 1 1/8" faceplate
- Standard "C", 6-pin cylinder
- ASA strike

► **For 2" up to 2 1/4" Thick Door Use PART# below**

CGN214T00 - Entrance, CGN00	CGN214T05 - Storeroom, CGN05
GN214T02 - Store Lock, GN02	CGN214T09 - Institution, CGN09
CGN214T03 - Classroom, CGN03	CGN214T20 - Privacy, CGN20
CGN214T04 - Communicating, CGN04	GN214T30 - Passage, GN30
Ⓜ <b>ICCGN214T00</b> - Entrance, <b>ICCGN00</b>	Available on <b>AT, SPA &amp; TUB</b> Design. Use same Part No.
Ⓜ <b>ICCGN214T03</b> - Classroom, <b>ICCGN03</b>	
Ⓜ <b>ICCGN214T05</b> - Storeroom, <b>ICCGN05</b>	

► **KEYWAYS**

6-pin solid brass "C" keyway standard. Optional: Schlage E, Schlage C-K, Russwin D1-2-3-4, Corbin 59/60, Corbin-Russwin L4, Sargent LA-LB-LC, Falcon/Weiser E, Arrow A, Yale 8, Yale GA and Kwikset. Can also accept Medeco, Assa, Kaba and *Cal-Royal HSK* High Security Cylinders.

► **TACTILE, LEAD LINING**

- Lead Lining Part # **LEAD**
- Tactile Part # **TAC**

► **MOUNT**

1 hole wooden mount  
Part# CGNMOUNT

► **ANTI MICROBIAL COATING**

Available on **US26D** finish only.  
Prefix "**ANTB**" before **PART#**.

► **ELECTRIFIED**

*Available on Storeroom Only*

- Electrified **Part #** ELEC,  
Specify 12V or 24V, fail safe (SAF) or fail secure (SEC)

<b>ELECTRIFIED</b>		
<b>DESCRIPTION</b>	<b>ITEM #</b>	<b>FINISHES</b> <small>(Finishes in bold are stock items)</small>
FAIL SAFE OPTION 12V AC/DC	ECGN0512SAF	<b>US26D, US10B, US4</b>
	EICCGN0512SAF	<b>US26D</b> , US10B, US4
	EICGYS0512SAF	US26D, US10B, US4
FAIL SECURE OPTION 12V AC/DC	ECGN0512SEC	<b>US26D, US10B, US4</b>
	EICCGN0512SEC	<b>US26D</b> , US10B, US4
	EICGYS0512SEC	US26D, US10B, US4
FAIL SAFE OPTION 24V AC/DC	ECGN0524SAF	<b>US26D, US10B, US4</b>
	EICCGN0524SAF	<b>US26D</b> , US10B, US4
	EICGYS0524SAF	US26D, US10B, US4
FAIL SECURE OPTION 24V AC/DC	ECGN0524SEC	<b>US26D, US10B, US4</b>
	EICCGN0524SEC	<b>US26D</b> , US10B, US4
	EICGYS0524SEC	US26D, US10B, US4