



- ***Grade 1***
- ***UL Listed***
- ***12 or 24 VDC***
- ***Low Current Draw***
- ***3-Year Warranty***

The Professional's Choice

The Command Access electrified version of the **Schlage ND80 series cylindrical** lock line allows for remote keyless access and egress control for heavy use applications where security and safety is critical. These locks may be purchased as complete locks or as modifications only (add MD prefix for modification only of customers' ND80 series). Along with the styles and finishes listed, we offer multiple functions and voltages to meet your requirements. Common applications include stairwell doors, lobby entrances, computer rooms, classrooms, interior and exterior doors.

U.S. Customer Support
1-888-622-2377

Visit our website for more details
www.CommandAccess.com

Canada Customer Support
1-855-823-3002

Models Available

CLN12EL/EU - storeroom:
(fail safe/fail secure)

Outside lever locked (EL) or unlocked (EU) electronically. Latchbolt retracted by lever inside. Switched power allows outside lever to retract latchbolt. Inside lever is always free for immediate egress.

CLN70PEL/EU - classroom:
(fail safe/fail secure)

Outside lever locked (EL) or unlocked (EU) electronically. Latchbolt retracted by key outside or lever inside. Switched power allows outside lever to retract latchbolt. Outside lever can be maintained unlocked by key. Inside lever is always free for immediate egress.

CLN80PEL/EU - storeroom:
(fail safe/fail secure)

Outside lever locked (EL) or unlocked (EU) electronically. Latchbolt retracted by key outside or lever inside. Switched power allows outside lever to retract latchbolt. Inside lever is always free for immediate egress.

CLN96PEL/EU - storeroom:
(fail safe/fail secure)

Outside lever locked (EL) or unlocked (EU) electronically. Outside clutching lever allows the lever to turn without retracting the latchbolt when locked. Latchbolt retracted by key outside or lever inside. Switched power allows outside lever to retract latchbolt. Inside lever is always free for immediate egress.

Trim Available

RHO, SPA & ATH

Finishes Available

605, 606, 612, 613, 625, 626

FEATURES:

- Continuous duty solenoids allow for “continuously on” applications such as Fail Safe or an unlock cycle
- Plug-in bridge rectifier that allows for an AC or DC power source
- Available with Schlage C type keyway standard (please inquire for all Schlage original keyways)
- No hassle 3-Year Warranty

OPTIONS:

- Available Fail Safe (Electrically Locked) or Fail Secure (Electrically Unlocked)
- Available “B” option for SFIC (small format interchangeable core) prep - less core
- Available “J” option for Schlage large format interchangeable core prep - less core
- Available “R” option for Schlage large format interchangeable core prep - with “C-keyway” core
- Voltage options - 12V or 24V (AC/DC)
- REX - Request to Exit or AE switch available (on all functions)
- CRU2 - Current Reduction Unit to improve solenoid life in “continuously on” applications
- CRU2i - The intelligent CRU2: automatically detects DC input voltage between 12 to 30 volts and converts it to operate our 12V locks. Additionally, it adjusts the current to the solenoid allowing the lockset to run cooler and last longer without any manual adjustments.

SPECIFICATIONS:

- Operating Voltage - 12 or 24VAC/DC (+or- 10%) (must specify 12 or 24 volts when ordering)
- Amperage - 12V = 250 mA / 24V = 150 mA
- Solenoid coil resistance - 12V = 49 Ω / 24V = 159 Ω
- Power consumption - 3 watts

Model No.	Notes:		
Customer:	Job No./Name:	Date:	Provided by: