

# ACA-ATR13 - RFID Tag

www.boschsecurity.com



**BOSCH**  
Invented for life



- ▶ Robust and reliable
- ▶ Water-resistant

The ACA-ATR13 proximity read-only tag offers universal compability with the Wiegand IF reader type W 3. The tag includes an embedded antenna, and an RFID integrated circuit enabling infinite numbers of reads by Wiegand type W3 readers.

The key-ring sized credential tag is durable with IP 68 and can be fully submerged, all the electronics is sealed inside.

## Technical Specifications

Type	Contactless passive
Materials	PVC / PET
IC Chip	EM4102
ISO Standard	ISO/IEC 10536
Environment class	IP 68
Operating frequency	125 kHz
Operating temperature	-20 °C to +50 °C (-4 °F to 122 °F)
Storage temperature	-20 °C to +50 °C (-4 °F to 122 °F)
Humidity	Up to 90% (non-condensing)

Surface finish	Matt
Antenna	Copper coil
Dimensions	54,5 x 35 x 7,3 mm (2.14" x 1.37" x 0.28")
Weight	9,6 g (0.331 oz)

## Ordering Information

### ACA-ATR13 - RFID Tag

125 kHz proximity read-only tag for Wiegand readers type W 3. Packing information: 25 tags/ each unit  
Order number **ACA-ATR13**

**Represented by:**

© Bosch Security Systems 2012 | Data subject to change without notice  
1371220619 | en, V1, 13. Apr 2012