19" Rack-Mount LCD Monitor





LED-1908HDR

This LED-backlit rack-mount LCD monitor features the latest technology with enhanced picture clarity and sharpness for both analog and digital video signals.

Benefits

Displays HD 1080i/p digital video LED backlight: brighter picture using less power Analog video is very clear with no detail loss 3D Comb Filter for better picture quality Durable metal case

Related Products

LED-1708HD: 17" standalone / wall-mount LCD Monitor LED-1708HDL: 17" flush-mount LCD Monitor LED-1708HDR: 17" rack-mount LCD Monitor LED-1908HDI: 19" standalone / wall-mount LCD Monitor LED-1908HDUB: 19" flush-mount LCD Monitor LED-1908HDVB: 19" standalone / wall-mount LCD High Brighness Monitor

Specifications	
Mount	Rack (9RU)
HD Compatible	Yes
Anti Glare Coating	Yes
Case	Durable Metal
Native Aspect Ratio	5:4, displays 16:9; True 4:3 option available
Visible Screen Size (WH)	14.8" x 11.8" / 376.3 x 301mm
Resolution	1280(H) x 1024(V)
Brightness Rating	300 cd/m ²
Contrast Ratio	10,000:1
Back Light	LED (30K)
PC Compatibility	Yes
Dot Pitch	0.294(H) x 0.294(V)mm
Colors	16.7M
Number of Pixels	1,310,720
Response Time	5ms (Rising/Falling)
Audio Power / Speakers	x2 1.5 Watts
Viewing Angle (L/R/T/B)	85/85/80/80 degrees
3D Comb Filter	Yes
Dimensions	9RU x 2.9"
Operating Temp	32 ~ 104°F / 0 ~ 40°C
Humidity	10% ~ 90%
Power Requirements	DC 12V (AC100~240)[50/60]
Power Consumption	15 Watts (Max)
Composite	x2 BNC Inputs / Outputs
VGA	x1 15 pin D-sub Input
HDMI	x1 Input
Audio	x1 RCA L/R Input; x1 PC stereo Input
Power	x1 2.1mm DC Input
Weight	Net: 12.43 lbs / 5.65 kg; Gross: 17.35 lbs / 7.9 kg
GSA	Yes

Specifications subject to change.