

AMX-HNC7V621-L1/28

2MP Covert Pinhole Network Camera-Lens Unit



WEC covert camera used modular design, this product provides an independent main unit (with 8-meters cable), while there is a main unit for customers to choose. It can be easily installed into any indoor environments, which makes this camera ideal for the ATMs (Automatic Teller Machines), banks, stores, hotels and offices.



MODEL(S) AVAILABLE

KEY FEATURES

- ▶ 1/2.8" 2MP progressive scan STARVIS™ CMOS
- ▶ Day/Night (Electronic), WDR
- ▶ 2.8mm Fixed Pinhole Lens
- ▶ 8-meters cable
- ▶ Require a Main Box to work together

Product Specifications

Camera	
Image Sensor	1/2.8" 2MP progressive scan CMOS
Effective Pixels	1920(H) × 1080(V)
Minimum Illumination	0.02 Lux @ F2.4 (Color, 1/3s, 30IRE) 0.08 Lux @ F2.4 (Color, 1/30s, 30IRE) 0.01 Lux @ F2.4 (B/W, 1/3s, 30IRE) 0.04 Lux @ F2.4 (B/W, 1/30s, 30IRE)
Lens Type	Fixed
Focal Length	2.8 mm
Max. Aperture	F2.4
Angle of View	Horizontal: 104° Vertical: 59° Diagonal: N/A
Optical Zoom	N/A
Close Focus Distance	N/A
Pan / Tilt / Rotaton	N/A

General	
Operating Temperature	-30°C ~ 60°C (-22°F ~ 140°F) / ≤ 95% RH
Storage Temperature	-30°C ~ 60°C (-22°F ~ 140°F) / ≤ 95% RH
Protection	N/A
Casing	Metal
Dimensions	48.65 mm × ø 30.5 mm (1.91" × ø 1.20")
Net Weight	400 g (0.88 lb)
Gross Weight	470 g (1.03 lb)
Certifications	CE (EN 60950:2000) UL:UL60950-1 FCC: FCC Part 15 Subpart B

Product Dimensions (mm [inch])

