

4MP 40X IR 350m Hybrid Smart-tracking PTZ




Hybrid



Ultra HD



VCA



Smart tracking



Perimeter



PoE++



IP67



350m

Key Spec:

- 1/2.7" progressive CMOS sensor(BSI+NIR+)
- Up to 4MP@30fps resolution
- Mini illumination:
Color: 0.005 lux @ (F1.2 AGC ON)
0 Lux with IR
- 40x(4.5-180mm) fast optical zoom and accurate focusing
- WDR, 3D DNR, Smart IR.
- Intelligent Video content analytics
- Smart tracking of human/vehicle
- Smart detection and perimeter protection
- ONVIF, API and SDK
- IP67,-40°C~65°C, Aluminum Alloy & Plastic
- PoE++ and DC24V
- Optional TVI/AHD/CVI Secondary output
- Optional Gyro based EIS option

Application:

Wide range area intrusion, perimeter protection and alarm and smart-tracking: such as airport, express way, parks, scenic spots, stations and venues, industrial park.

SPECIFICATION:

Camera Module		IP-5PT4IE3-40X				
Image sensor	1/2.7" BSI+NIR progressive scan CMOS					
Mini. Illumination	Color: 0.005Lux @ (F1.2, AGC ON); B/W: 0.001Lux @(F1.2, AGC ON); 0 Lux with IR					
Image setting	Flip, Mirror, Saturation, Brightness, Contrast, Sharpness, AGC, etc. adjusted by client					
Shutter Speed	50Hz: 1/25 s – 1/25,000 s; 60Hz: 1/30s-1/30,000					
White Balance	Auto/Manual/Indoor/Outdoor					
Gain control	Auto/Manual					
Day & Night control	Auto/Manual ,time schedule					
Iris control	Auto/Manual					
SNR	≥52dB					
3D DNR	Auto/Manual					
AE Enhancement	BLC, HLC, WDR					
Privacy Mask	4 areas, up to 4 mask in the same frame					
EIS	Optional Built-in gyro sensor for electrical image stable within 30x-40x (TBC)					
Picture overlay	Logo picture could be overlaid on video with 128x128pixels,24bits BMP format					
OSD overlay	max 15 characters/line, 8 lines, white or red font color					
OSD Menu	N/A				including all camera parameters and settings	
Lens						
Focus length	f=4.5 ~ 180mm lens, 40x optical zoom					
Zoom Speed	Approx. 5.2s (optical zoom, wide-tele)					
Field of View	H: 62.4° ~ 1.9°; V: 35.3° ~ 1° ; D: 70.24° ~ 2.1° (wide-tele)					
Working distance	wide: 1.0m ~ INF; tele: 1.5m ~ INF					
Iris Property	F1.2 ~ F3.5 (wide-tele); DC-IRIS (hall sensor ,16Stops)					
IRCUT type	Removable IRCUT filter					
DORI distance	Focus length	Detect(25px/m)	Observe(63px/m)	Recognize(125px/m)	Identify(250px/m)	
	f=4.5mm	90m (295 f.t.)	35.71m (117 f.t.)	18m(39 f.t.)	9m(29.5 f.t.)	
	f=180mm	3060m(10039 f.t.)	1428.5m(4687 f.t.)	720m (2362 f.t.)	360m(1181 f.t.)	
PTZ						
Gimbal	Vertically: dual belts for backup ,Horizontally: Gear-Box, 1024 steps encoder					
Pan Range	360°endless					
Pan speed	Configurable, from 0.05°-450°/s; Preset speed: 540°/s					
Tilt Range	From -20° to 160°,auto flip					
Tilt Speed	Configurable, from 0.05°~ 270°/s, Preset speed: 360°/s					
Proportional Zoom	Yes					
Preset	360					
Cruise	8 cruises, up to 16 presets for each cruises					
Trace	4 traces, record time over 3 minutes for each trace					
Power off memory	Support					
Action mode	Preset/Cruise/Trace/Auto Scan/Random Scan					
3D Positioning	Support, Software set or hardware auto detection, by built-in gyro sensor. TBC.					
PTZ Position Display	Support					
Schedule Task	Preset/Cruise/Trace/Random Scan/Boundary Scanning /Dome reboot					
IR						
IR Distance	350m /1148 f.t., 8pcs 4 groups of dual stacks IR Arrays					
Smart IR	Yes					
Network						
Max Resolution	2880x1620 (16:9 aspect ratio)					
Main stream	50Hz: 25fps: 2880x1620, 2560x1440,1920x1080,1280x960,1280x720, 60Hz: 30fps: 2880x1620, 2560x1440,1920x1080,1280x960,1280x720					
Sub stream	50Hz: 25fps: (704 × 576, 640 × 480, 352 × 288); 60Hz: 30fps (704 × 480, 640 × 480, 352 × 240)					

Third Stream	50Hz:25/50fps (1920 × 1080, 1280 × 960, 1280 × 720, 704 × 576, 640 × 480, 352 × 288) 60Hz:30/60fps (1920 × 1080, 1280 × 960, 1280 × 720, 704 × 480, 640 × 480, 352 × 240)	
Video compression	H.265+/H.265/H.264+/H.264/MJPEG	
H.264 Standard	H.264/AVC codec BP/MP/HP, Level 5.1	
H.265 Standard	H.265/HEVC codec MP, level 5.0	
Video Bit Rate	64 Kbps to 8Mbps	
Audio compression	G.711 A/U	
Audio Bit Rate	64K bps	
Protocols	HTTP, HTTPS, IPv4/IPv6, 802.1x, QoS, FTP, SMTP, UPnP, SNMP,DNS, DDNS, NTP, RTSP, RTCP, RTP, TCP/IP, UDP, DHCP, PPPoE	
User / Host	Up to 16 users, 3 levels: Administrator, Advanced User and Normal User	
Security Measures	User authentication (ID and PW), Host authentication (MAC address); HTTPS encryption, IEEE802.1x port-based network access control; IP address filtering	
Smart Features		
Basic event	Motion detection, Video tampering alarm, Exception(Network disconnected, IP address conflict, SD full, SD error)	
Face recognize	Detecting max 15 faces at same scene. Detecting, tracking, capturing	
Road traffic	Vehicle detecting and tracking	
Smart Detection	Tripwire, Bi-directional tripwire, Illegal intrusion detection, Region entrance detection, Region exiting detection, Unattended baggage detection, Object removal detection, etc.	
Smart Tracking	Smart tracking of human or vehicle, auto/manual	
System Integration		
Alarm Interface	1 Alarm input(Dry contact); 1 Alarm output	
Audio Interface	1 audio input, line level, 2.0-2.4Vpp,impedance 1KΩ; 1 audio output, line level, impedance,600Ω	
Alarm Linkage	Alarm actions, such as Preset, Cruise, Trace, Memory Card Video Record, Trigger Recording, Notify Surveillance Center, Upload to FTP/Memory Card, Send Email, etc.	
Network Interface	1 RJ45 10M/100M Adaptive Ethernet ,Support PoE++	
SD Card Slot	One MicroSD slot and chamber, up to 256G	
Built-in Speaker & Mic	N/A	
RS 485	N/A	Half-duplex mode ,support Titanium-VISCA,Pelco-P/D protocol
BNC		TVI4.0/AHD2.0/CVI/CVBS, Support COC protocol
Mode Switch		12Bits ,support baud rate, address, TVI/AHD/CVI mode
Reset button	Yes	
Heater	Yes	
Fan	Yes	
Water removal	Remove water-drops by quick spinning	
API	ONVIF, support Titanium SDK and third-party management platform	
Client	Titanium NVR,NVMS; and the third-party client	Titanium DVR, NVR,NVMS; and the third-party client
Web Browser	IE8-11	IE8-11
General		
languages	Czech; English, German ; Hungarian ; Italian ; Japanese ; Korean ; Portuguese, Polish; Russian, Romanian, Spanish; Spanish(Mexico); Simplified Chinese; Turkish; Traditional Chinese. Etc.	
Power supply	DC24V±25% ,PoE++ (802.3.bt), max 34W include IR ON+PTZ working	
Working condition	-40°C ~ 65°C (-40°F ~ 149°F), IR off; -40°C ~ 45°C(-40°F ~ 113°F),IR on; Cold start at - 30°C; 90%RH	
Storage condition	-40°C ~ 70°C ; ≤ 95% RH	
Protection	6000V Lightning Protection, Surge Protection and Voltage Transient Protection	
Material	Aluminum Alloy + Plastic	
Dimensions	Φ 300mm × 197mm (Φ11.8 inch × 7.75 inch)	
Net Weight	Approx. 4.5 Kg (9.92 lb.) TBC	
Certification	IP67,IK10 (including glass window), ROHS, CE, FC	

Dimensions(mm):

