

C-ML

AUDIO MONITORING SYSTEM INSTALLATION AND OPERATING INSTRUCTIONS

DESCRIPTION

The Model C-ML is an omni-directional, low impedance, electret condenser microphone with mic level audio. It is housed in a high impact ABS tube designed for mounting in special or customized housing. Normal pick-up pattern is approximately 15' from the microphone location, all directions, or within 30' diameter circle. The unit comes with 20' pre-made cable with a stereo plug on one end that can be plug directly to the Audio Input of an IP camera.






Microphone Element

SPECIFICATIONS

Sensitivity	-45 dB/pa
Frequency response	50 Hz to 8 kHz
Output Impedance	1kΩ
Current drain	0.8mA
Supply voltage	1.8Vdc to 4.5Vdc
Microphone housing	High impact ABS
Dimensions	0.455" dia
Weight Shipping Weight	4.5 oz 1 lb

MICROPHONE CONNECTION

Connect the other end of the cable with a 3.5mm Stereo Plug to the Audio Input of the IP camera. The camera has to be configured to Mic level settings.



WARRANTY

LOUROE ELECTRONICS® warrants that at the time of shipment products manufactured by LOUROE ELECTRONICS® to be free of defects in material and workmanship. Should a defect appear within one year (12 months) from date of shipment, LOUROE ELECTRONICS will, at its sole discretion, repair or replace the defective equipment. This equipment shall not be accepted for repair or return without prior notification by LOUROE ELECTRONICS®.

This warranty does not extend to any Louroe product that has been subjected to improper or incorrect installation, misuse, accident, or in violation of installation instructions provided by LOUROE ELECTRONICS.

Returned shipments to LOUROE ELECTRONICS® shall be at customer's expense. LOUROE ELECTRONICS® will return the equipment prepaid via best way.