

## DESCRIPTION

Louroe Model E-ML is an omni-directional, mic level low impedance, electret condenser microphones. It can pick up normal sounds approximately 15' away if mounted to a wall, or within a 30' circle if ceiling mounted. The microphone is mounted inside a single Bell Box for outdoor of in a moist environment. The unit comes with with pre-made 20' cable with stereo plug for direct connect to the audio input of the IP camera.

## APPLICATION

The Model E-ML Microphones can be used in situations such as:

- Parking structures
- Secured walkways
- Maintenance yards
- Building peripherals
- Entry gates
- Gas Stations
- Any area requiring protection from weather

## MODEL E-ML MICROPHONE



## FEATURES

- Easy connection to an IP camera
- Microphone can pick up normal sounds 15' away
- Mounts inside a standard single gang Bell Box for surface mounting
- May be located up to 20' from IP Camera or pre-amp.
- Used in moist or damp environment

### IMPORTANT NOTICE

When this equipment is used as part of an audio monitoring system, the law requires that the public be given notice of AUDIO MONITORING ON THE PREMISES. A decal notice is included with each microphone shipped.



Federal Law References:  
 Federal Regulations, US Code, Title 18.  
 Crime and Criminal Procedure, Sec 2510.



## SPECIFICATIONS

▪ Sensitivity	-45 dB/pa
▪ Frequency response	50 Hz to 8 kHz
▪ Output Impedance	1kΩ
▪ Current drain	0.8mA
▪ Supply voltage	1.8Vdc to 4.5Vdc
▪ Microphone faceplate	Stainless steel
▪ Dimensions	2 3/4" W x 4 1/2" H
▪ Weight	15.5 oz
▪ Shipping Weight	1 lb