



DESCRIPTION


The Model TLSP Corner Mount is a two-way talk/listen speaker/microphone with built-in electret condenser microphone and a 3" speaker. Vandal resistant housing is especially designed for mounting in a corner or between wall and ceiling. When part of a Louroe Audio System, TLSP Corner Mount provides listen and talkback capabilities between the remote area and the Louroe Base Station.


APPLICATION

- Correctional Facilities
- Transportation Terminals
- Juvenile Facilities
- Public Acces Areas
- Parking Structures
- Areas where vandalism is a concern

WIRING REQUIREMENTS

- 4 Conductor consisting of:
- 2 Conductor shielded, 20 gauge with 22 gauge drain (microphone connection)
- 2 Conductor unshielded, 18 gauge (speaker connection) All in the same jacket









TLSP CORNER MOUNT



- Vandal resistant 18 gauge CRS housing Mounts in a corner or between wall and ceiling
 Ease dimensional 8 3 (u Cⁿ)
- Face dimensions: 8 ³/₄ x 6"
- May be mounted up to 1,000 ft. from Louroe Base Station
- Powered from the Louroe Base Station
- Microphone can pick up normal sounds 15' away or within a 30' dia. circle

SPECIFICATIONS (MICROPHONE)

Sensitivity	-45 dBV/Pa 1 Pa = 94 dB SPL
Frequency Response	50 Hz to 15 kHz
Output	Line Level (0 dBV, 600 Ω @ 1kHz)
Current Drain	10mA
Supply Voltage	12 Vdc

SPECIFICATIONS (Speaker)

	-
Power rating	7W
Input	70.7V constant
Frequency response	300 Hz to 4 kHz
Voice coil impedance	8Ω
Speaker size	3"
Dimensions	10" L x 6" W x 4 1/2" D
Material	Steel
Weight	2 lb 13 oz
Shipping Weight	4 lbs