



KPM-19-43 19" LED Monitor

Model	KPM-19-43
Screen Size	19"
Resolution	1280 x 1024 @ 60Hz
Brightness	250cd/m ²
Contrast Ratio	1000:1
Aspect Ratio	5:4
Viewing Angle (H/V)	170° / 160°
Pixel Pitch	0.294mm x 0.294mm
Display Colors	16.7 Million
Response Time	<5ms
Video System	NTSC / PAL
Scanning Frequency	(H) 31~80 KHz/ (V) 56 ~ 75 Hz
HDMI-In	1
VGA-In	1
BNC-In/Out	1/1
OSD Language	English, Spanish, French, German, Italian, Portugese, Netherlands
Dimensions (W x H x D)	16.61" x 15.28" x 7.68" (422 x 388 x 195mm)
Net Weight	10.58lbs (4.8KG)
Tilt Stand / Tilt Range	Fr: 5 / Rear: 15
Cabinet Materials	Plastic
Color	Black
VESA Mount	100mm x 100mm (M4 x 10mm Screw)
MTBF (Approx)	30,000 Hours
Power Consumption	<20W
Power Source	100~240VAC
Operating Temperature	32° ~104° F / 0° ~ 40° C
Approvals	FCC
Included Accessories	VGA Cable

Features:

- Suitable for every Video Surveillance and Security application: displays HDMI digital plus VGA and BNC analog inputs (with looping BNC analog output)
- Superlative image quality with 16.7 million color capability
- HD 1280 x 1024 resolution
- 3D Comb Filter/De-interlace
- Customizable video settings in flexible On Screen Display (OSD) Menu with 7 language options
- Auto-on when VGA or HDMI DVR/NVR video is detected
- Bright LED illuminated panel with 170° H viewing angle
- LED panel conserves energy and extends service life
- Included desk stand is easily removable to accommodate most 100mm VESA mounts

Ordering Info:

KPM-19-43: 19" LED Monitor

KT&C America, Inc. reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.

KT&C America, Inc.

New Jersey Office
40 Lane Road 1st Floor
Fairfield, NJ 07004
T: 973-276-0118
F: 973-276-0116

New York Office
200 Pkwy Drive South Suite 200
Hauppauge, NY 11788
T: 631-864-0118
F: 631-864-0116

California Office
3240 Wilshire Blvd Suite 501
Los Angeles, CA 90010
T: 213-381-0061
F: 213-381-0064

www.ktncusa.com